

# ZL-S4020/4021

4U/19-inch standard Industrial chassis supports up to E-ATX (12"x13") motherboards



## Features

- 主板最大支持ATX及以下规格
- 12Gb/s直连背板，兼容SAS/SATA硬盘
- 支持标准ATX电源或1+1冗余电源
- 智能温控，最多支持3x12038插拨风扇+后置2x8038+1x12038后挂风扇
- 后置7槽全高PCIe扩展卡位

## 技术参数

机箱形态	机架式
机箱高度	4U
适应主板	E-ATX/ATX/Micro-ATX及以下
背板	12Gb/s直连背板
磁盘位	支持SGPIO，兼容SAS3.0/SATA3.0硬盘，标配支持8块3.5" (或2.5")热插拔硬盘位 和2块2.5" 内置非热插拔扩展位
硬盘防震	硬盘架采用EMI弹片设计，独有防震风扇设计，降低风扇与硬盘间共振，不影响硬盘I/O速度
系统风扇	支持智能温控，标配3个12038插拨风扇，最多支持3x12038插拨风扇+后置2x8038+1x12038后挂风扇
扩展卡位	7个全高的PCIe扩展卡位
前板控制	2个USB2.0，1个开关键，1个重启键，1个UID，1个硬盘指示灯，1个系统故障灯，2个网络指示灯
滑轨	选配
产品材质	进口SGCC(镀锌钢板)
机箱尺寸	650 x 437 x 176mm
机箱毛重	15KG
包装尺寸	880 x 580 x 310mm

## Technical Parameter

Chassis style	rack type
Chassis height	4U
Supported Motherboards	E-ATX/ATX/Micro-ATX and below
backplane	12Gb/s direct connect backplane
Disk slot	Support SGPIO, compatible with SAS3.0/SATA3.0 hard drives, standard support for 8 3.5 "(or 2.5") hot swappable hard drive slots and 2 2.5 "built-in non hot swappable expansion slots
Hard drive shockproof	The hard drive rack adopts EMI shrapnel design and a unique shock-absorbing fan design to reduce resonance between the fan and the hard drive, without affecting the I/O speed of the hard drive
System fan	Supports intelligent temperature control, comes standard with 3 12038 plug-in fans, supports up to 3x12038 plug-in fans+rear 2x8038+1x12038 rear mounted fans
Expansion slot	7 full height PCIe expansion card slots
Front panel control	2 USB 2.0, 1 power button, 1 restart button, 1 UID, 1 hard drive indicator light, 1 system fault light, 2 network indicator lights
Sliding rail	Optional
Product Material	Imported SGCC (galvanized steel sheet)
Case size	650 x 437 x 176mm
Case gross weight	15KG
Package dimensions	880 x 580 x 310mm

