

ZL-S2030/2031

2U/19-inch standard server chassis,
supports up to E-ATX motherboards



Features

- 主板最大支持E-ATX (12"x 13") 及以下规格
- 单组8xU.2接口, PCIE x 4 Gen5/兼容8路SATA资源
- 支持单电或者1+1冗余电源
- 智能温控, 最多支持4*8038插拔风扇
- 可选横插全高双位卡

技术参数

机箱形态	机架式
机箱高度	2U
适应主板	E-ATX/ATX/Micro-ATX及以下
背板	单组8 x U.2接口, 最大支持3组(24个2.5HDD)
磁盘位	SSD: 8 x U.2接口, 支持2.5寸SSD, PCIE x 4 Gen5, 或SATA总线 MCIO: 4 x MCIO 8i Gen5, 提供8路PCIE x 4 Gen5 资源 SLIM-SAS: 提供8路SATA 资源
硬盘防震	硬盘架采用EMI弹片设计, 独有防震风扇设计, 降低风扇与硬盘间共振, 不影响硬盘I/O速度
系统风扇	支持智能温控, 标配3个8038热插拔风扇, 最大支持4个8038热插拔风扇
扩展卡位	7个半高的PCIe扩展卡位, 可选配2个横转全高扩展卡位 + 一个半高横转扩展卡
前板控制	2个USB 2.0, 1个开关键, 1个重启键, 1个UID, 1个硬盘指示灯, 1个系统故障灯, 2个网络指示灯
滑轨	选配
产品材质	进口SGCC(镀锌钢板)
机箱尺寸	670 x 450 x 88mm
机箱毛重	10.8KG
包装尺寸	880 x 580 x 220mm

Technical Parameter

Chassis style	rack type
Chassis height	2U
Supported Motherboards	E-ATX/ATX/Micro-ATX and below
backplane	12Gb/s direct connect backplane
Disk slot	SSD: 8 x U.2 interface, supports 2.5-inch SSD, PCIE x 4 Gen5, or SATA bus MCIO: 4 x MCIO 8i Gen5, Provide 8 PCIE x 4 Gen5 resources SLIM-SAS: Provides 8 SATA resources
Hard drive shockproof	The hard drive rack adopts EMI shrapnel design and a unique shock-absorbing fan design to reduce resonance between the fan and the hard drive, without affecting the I/O speed of the hard drive
System fan	Supports intelligent temperature control, comes standard with 3 8038 hot swappable fans, and can support up to 4 8038 hot swappable fans
Expansion slot	7 and a half height PCIe expansion card slots, optional with 2 horizontal full height expansion card slots and 1 half height horizontal expansion card
Front panel control	2 USB 2.0, 1 power button, 1 restart button, 1 UID, 1 hard drive indicator light, 1 system fault light, 2 network indicator lights
Sliding rail	Optional
Product Material	Imported SGCC (galvanized steel sheet)
Case size	670 x 450 x 88mm
Case gross weight	10.8KG
Package dimensions	880 x 580 x 220mm

