

ZL-S1010/1011

**1U/19-inch standard Industrial chassis,
supports up to E-ATX (12"x 13")
motherboards**



Features

- 主板最大支持E-ATX (12" x 13") 及以下规格
- 直连SAS/SATA背板, 或者可选4.0 NVMe/SAS/SATA背板
- 支持单电或者1+1(1u冗余电源)
- 智能温控, 最多支持6 x 4056/4028插拔风扇
- 支持全高卡X1

技术参数

机箱形态	机架式
机箱高度	1U
适应主板	E-ATX/ATX/Micro-ATX及以下
背板	直连SAS/SATA背板, 或者可选4.0 NVMe/SAS/SATA背板
磁盘位	支持SGPIO, 兼容SAS3.0/SATA3.0硬盘, 标配支持4块3.5" (或2.5") 热插拔硬盘位
硬盘防震	硬盘架采用EMI弹片设计, 独有防震风扇设计, 降低风扇与硬盘间共振, 不影响硬盘I/O速度
系统风扇	支持智能温控, 标配3个4056防震风扇, 最大支持6个4056/4028防震风扇
扩展卡位	1个全高横向的PCIe扩展卡位, 标配PCIe转接卡
前板控制	2个USB2.0, 1个开关键, 1个重启键, 1个UID, 1个硬盘指示灯, 1个系统故障灯, 2个网络指示灯
滑轨	选配
产品材质	进口SGCC(镀锌钢板)
机箱尺寸	670 x 437 x 44mm
机箱毛重	9KG
包装尺寸	880 x 580 x 175mm

Technical Parameter

Chassis style	rack type
Chassis height	1U
Supported Motherboards	E-ATX/ATX/Micro-ATX and below
backplane	Directly connected to SAS/SATA backplane, or optional 4.0 NVMe/SAS/SATA backplane
Disk slot	Support SGPIO, compatible with SAS3.0/SATA3.0 hard drives, standard support for 4 3.5 "(or 2.5") hot swappable hard drive slots
Hard drive shockproof	The hard drive rack adopts EMI shrapnel design and a unique shock-absorbing fan design to reduce resonance between the fan and the hard drive, without affecting the I/O speed of the hard drive
System fan	Supports intelligent temperature control, comes standard with 3 4056 shock-absorbing fans, and can support up to 6 4056/4028 shock-absorbing fans
Expansion slot	1 full height horizontal PCIe expansion card slot, standard PCIe adapter card
Front panel control	2 USB 2.0, 1 power button, 1 restart button, 1 UID, 1 hard disk indicator light, 1 system fault light, 1 network indicator light
Sliding rail	Optional
Product Material	Imported SGCC (galvanized steel sheet)
Case size	670 x 437 x 44mm
Case gross weight	9KG
Package dimensions	880 x 580 x 175mm

